


## LEGEND

- Brake housing
- Speed housing
- Seatpost housing
- Housing outside the frame
- - - Housing inside the frame



## BRAKE HOUSING

**Step 1** | Secure the brake housing to the base brackets. Tuck the brake housing into the cavity located on the motor mount.

**Step 2** | Tuck the brake housing inside the down tube and attach it to the left guide of the down tube.

**Step 3** | Pull the brake housing out through the upper cavity of the front left stopper located at the top of the down tube.

## SPEED HOUSING

**Step 1** | Thread the housing through the front opening of the base so it pops out at the back.

**Step 2** | Thread the rear gear housing through the cavity on the motor support.

**Step 3** | Tuck the rear gear housing inside the down tube and attach it to the left stopper inside the down tube.

**Step 4** | Pull out the rear gear housing by the lower left stopper located at the top of the down tube.

## MECHANICAL SEATPOST HOUSING

**Step 1** | Thread the dropper housing through the seat tube and bring out through the battery holder.

**Step 2** | Tuck the dropper housing inside the down tube and attach it to the right stopper inside the down tube.

**Step 3** | Pull out the dropper housing by the right stopper located at the top of the down tube.


## HYDRAULIC SEATPOST HOUSING

**\*\* Perform the same steps as for the mechanical dropper but start with Step 2 and finish with Step 1.**

#### LEGEND

- Switch
- DI-2 cable
- Charging port
- Speed sensor

- Housing outside the frame
- - - Housing inside the frame




## SWITCH

**Step 1** | Position the spacer and enter the switch wire in the location provided on the top tube until the switch is in place.

**Step 2** | Pull out the switch cable at the end of the battery compartment and secure to the right compartment stopper.

**Step 3** | Connect the wire to the motor and secure the switch.



## SPEED SENSOR

**Step 1** | Thread the cable through the inside of the seat stay. Pull the cable out through the cavity inside the seat stay.

**Step 2** | Secure the sensor cable to the base guides and fit into the same cavity as the brake housing, located at the motor mount.

**Step 3** | Connect the cable to the motor.

## CHARGING PORT

**Step 1** | Tuck the end of the charging cable through the oval cavity under the front of the down tube. Attach the cable to the left inner stopper.

**Step 2** | Plug into the battery holder.

## DI-2 CABLE


**Step 1** | Thread the conductor cable through the upper cavity of the right front stopper located at the top of the down tube.

**Step 2** | Pull the cable out through the motor opening.

## LÉGENDE

- Brake housing
- Speed housing
- DI-2 cable
- Charging port
- Switch
- Seatpost housing

Secure the housings and cables to the guides with clips inside the frame.



# DeVinci

TECHNICAL MANUAL  
E-MTB AC-DC& EP



## PLEASE READ BEFORE USING YOUR BIKE

Even if you have already piloted a bike for years, it is important to be aware of the information contained in the "User Manual" and the Specific Manual (Power-Assisted Bike) PAB carefully before riding your new "AC, DC or EP".

- These documents contain important information.
- Understand the use, layout and maintenance of each electrical component of your new PAB.

**Your safety and those of other users is paramount.**

- Never ride the bike without its battery; the battery must be on the bike when you head out, otherwise there will be no lights on the bike.
- Never ride the bike without a saddle; failure to comply with this rule could lead to accidents.
- Inspect your bike to make sure there are no loose screws or components, or damages. In the event of a defect, visit your authorized Devinci retailer for repair.
- A PAB is faster than a normal bike; risks of accident with other users on the road may occur.
- Ride under the conditions mentioned below: (List the type of appropriate conditions for the bike).
- For PAB's that have a rear rack: the limit is 20 kg.

**The electrical system requires careful handling:**

- Do not clean the bike with a high-pressure jet. The system is sensitive to moisture. High-pressure water may seep into the connectors or other parts of the electrical system.
- Handle the battery carefully and pay attention to electric shocks. Failure to comply with this instruction could lead to abnormal heating or severe damage. In very rare cases, the consequences of an electrical shock could lead to a fire. In case of doubt, have the battery inspected by an authorized Devinci retailer

**Perform maintenance of the battery as mentioned in the Technical Manual:**

**Note: Failure to follow the instructions below may damage the battery and require you to purchase a new battery kit.**

- Charge the battery only with the Shimano charger.
- When the battery is not used for a long time, recharge it to 100% (from 4 to 5 LEDs on the charge indicator).
- Check the battery charge status regularly when not in use, recharge it to 100% if the load is less than 20% (1 indicator light on the charge gauge). Check the load at least every month and have it fully charged every 6 months.
- It is not recommended to keep the battery connected to the charger for a long period.
- If the battery remains uncharged for a long time, it can lose a significant part of its effectiveness.
- Store the battery in a well-ventilated and dry place. Pay attention to moisture.
- In case of poor conditions, remove the battery from the bike and store it in a dry place until next use.
- The battery can be stored at temperatures between -10°C and 40°C. For long service life, store it at a temperature close to 20°C.
- Monitor the storage temperature and try to avoid discrepancies. For example, do not leave the battery in your car during summer or leave the battery outdoors during a storm in winter.
- It is recommended to store a battery which is not connected to the bike.

**Follow the transport instructions for your PAB:**

- Remove the battery, the control screen and (if necessary) the baskets, arrange them elsewhere in a vehicle during transport.
- Comply with local laws regarding transportation of the PAB.
- A PAB is heavier than a normal bike, so you must be careful when transporting it. Check that the maximum load of the rack, roof or bike rack used is respected. Refer to the support manual used.
- The Li-Ion battery of your PAB, due to its size, is considered a "Class 9 dangerous goods" during transport. Applicable regulations could limit transport of a separate Li-Ion battery (when the battery is not on the bike) in some places. This regulation applies to several airlines and a number of road transport companies. On the other hand, if you are planning to move around with a full PAB (when the battery is on the bike), regulations are less strict. In case you use these transport methods, check the regulations that apply to your PAB with your transport company, before booking.

**Visit your authorized Devinci retailer for regular maintenance of your new PAB:**

- Only your retailer has the know-how and the proper equipment to maintain your PAB.
- If you have any questions about your PAB, please ask for assistance from your retailer!



## ABOUT OUR MANUALS

Our user manuals meet EN 15194, 14766 standards.

Like many sports, cycling involves risk of injury and accidents, so you must be fully aware of these risks. Neither the manufacturer, the retailer, nor the person who sold you the bike, nor the people who maintain the trails are responsible for these risks. As you are solely responsible, it is, therefore, essential that you read and fully understand all the parts contained in this manual and the user manual.

To enjoy maximum safety and enjoyment right from the get go, it is important that you are familiar with your new bike, its handling and its possibilities. It is your duty to maintain your bike well and reduce the risk of injury. Biking can be a dangerous activity, even under the best conditions. There are risks associated with using a bicycle that cannot be predicted or avoided. These are the sole responsibility of the cyclist.



## YOUR AUTHORIZED DEVINCI DEALER


Your authorized Devinci retailer is at your service to guide your choices of bike and accessories which are best suited to the style of biking you wish to perform. This will help you maintain your equipment in good condition so that you can take full advantage of your investment. The staff at your authorized Devinci retailer have the training, experience and tools to carry out the right repairs and provide you with reliable advice.

However, your authorized Devinci retailer cannot make decisions for you, and cannot be held responsible for your lack of knowledge, experience, qualification or common sense. However, it will take the necessary time to explain the operation of a component or to help you choose an accessory that meets your specific needs.

For further information, please see the **User Manual** available on the Devinci website and the **Shimano STEPS EP800 & E7000 series user manual** available on <http://si.shimano.com/>. You can ask your authorized Devinci retailer. He will take the time to answer any questions you may have and will advise you, with great pleasure.


To learn more about your bike's warranty, refer to the User Manual under the "Ride in Peace with the Devinci Warranty" tab.





**DO PIVOT**

AC-DC		
ITEMS	#SERVICE KIT	DESCRIPTION
1	KFC19040	Bearing kit AC/DC/EP
2	KFC19041-01	AC/DC/EP Shock bolt Black
3	KFC11051	Derailleur Hanger Split Pivot 12x142/148
4	KFC19011	Rear Axle Boost148*12mm/201mm
5	KFC00001	Battery Protector AC/DC/EP
6	KFC00004	Motor Protector AC/DC EP800
7	KFC19043	Chainstay Protector kit AC/DC/EP
8	KFC19044	Cable Guide kit AC/DC/EP
9	KFC00003	Satellite parts spacers AC/DC/EP
10	KFC19045-01	Pivot kit Shaft AC/DC/EP Black





#### **ASSEMBLY INSTRUCTIONS:**


- 1- THOROUGHLY CLEAN THE INTERIOR OF EACH BEARING HOUSING TO REMOVE ANY DIRT OR OLD GREASE;
- 2- APPLY HIGH QUALITY WATERPROOF GREASE ON THE INSIDE FACE AND INSIDE DIAMETER OF ALL BEARING HOUSINGS BEFORE PRESS-FIT;
- 3- APPLY HIGH QUALITY WATERPROOF GREASE TO ALL PIVOT PARTS THAT CONTACT WITH THE INNER DIAMETER OF THE BEARINGS.
- 4- APPLY HIGH QUALITY WATERPROOF GREASE TO ALL NON-THREADED METAL-TO-METAL INTERFACES (EX.: PLANAR FACE OF THE PIVOT SPACER THAT CONTACTS THE LATERAL FACES OF THE FRONT TRIANGLE WL PIVOT). THESE INSTRUCTIONS ALSO APPLY TO THE SHOCK ASSEMBLY;
- 5- UNLESS OTHERWISE SPECIFIED, APPLY BLUE LOCTITE 242 ON ALL THREADS BEFORE ASSEMBLY TO THE SPECIFIED TORQUE VALUE;
- 6- TO PREVENT DAMAGE TO THE FRAME, THE SEATPOST MUST HAVE A MINIMUM INSERTION IN THE SEAT TUBE.

#### **ALUMINIUM FRAME:**

SMALL / MEDIUM / LARGE / X-LARGE - 100mm INSERTION

\*ALWAYS VERIFY CONNECTOR CLEARANCE BEFORE FULLY INSERTING A DROPPER POST.

7- **FRG ADJUSTABLE:** THIS DESIGN ALLOWS RIDERS TO CHOOSE BETWEEN A LOW OR HIGH POSITION. WITH FRG ADJUSTABLE TECHNOLOGY, YOU CAN FINE-TUNE YOUR RIDE TO PERSONAL TASTES OR SPECIFIC TRAIL TYPES USING A FLIP-FLOP PIVOT MECHANISM THAT SLIGHTLY CHANGES THE BIKE'S GEOMETRY AS SHOWN BELOW.



#### **CLEANING INSTRUCTIONS:**

IT IS A WELL KNOWN FACT THAT A CLEAN BIKE PERFORMS BETTER. DEVINCI RECOMMENDS WASHING YOUR BIKE REGULARLY USING A BRUSH AND SOAPY WATER. HOWEVER, DEVINCI DO NOT RECOMMEND THE USE OF A PRESSURE WASHER, SINCE THIS MAY SIGNIFICANTLY REDUCE THE SERVICE LIFE OF BALL BEARINGS. EVEN THOUGH OUR BALL BEARINGS ARE EQUIPPED WITH HIGH QUALITY DOUBLE-LIP SEALS, HIGH PRESSURE WATER CAN STILL PASS THESE SEALS AND REMOVE THE GREASE INSIDE THE BEARING. THIS MAY CAUSE PREMATURE CORROSION AND WEAR OF THE BALL BEARINGS.

# DeVinci

TECHNICAL MANUAL  
E-MTB AC-DC& EP



## PLEASE READ BEFORE USING YOUR BIKE

Even if you have already piloted a bike for years, it is important to be aware of the information contained in the "User Manual" and the Specific Manual (Power-Assisted Bike) PAB carefully before riding your new "AC, DC or EP".

- These documents contain important information.
- Understand the use, layout and maintenance of each electrical component of your new PAB.

**Your safety and those of other users is paramount.**

- Never ride the bike without its battery; the battery must be on the bike when you head out, otherwise there will be no lights on the bike.
- Never ride the bike without a saddle; failure to comply with this rule could lead to accidents.
- Inspect your bike to make sure there are no loose screws or components, or damages. In the event of a defect, visit your authorized Devinci retailer for repair.
- A PAB is faster than a normal bike; risks of accident with other users on the road may occur.
- Ride under the conditions mentioned below: (List the type of appropriate conditions for the bike).
- For PAB's that have a rear rack: the limit is 20 kg.

**The electrical system requires careful handling:**

- Do not clean the bike with a high-pressure jet. The system is sensitive to moisture. High-pressure water may seep into the connectors or other parts of the electrical system.
- Handle the battery carefully and pay attention to electric shocks. Failure to comply with this instruction could lead to abnormal heating or severe damage. In very rare cases, the consequences of an electrical shock could lead to a fire. In case of doubt, have the battery inspected by an authorized Devinci retailer

**Perform maintenance of the battery as mentioned in the Technical Manual:**

**Note: Failure to follow the instructions below may damage the battery and require you to purchase a new battery kit.**

- Charge the battery only with the Shimano charger.
- When the battery is not used for a long time, recharge it to 100% (from 4 to 5 LEDs on the charge indicator).
- Check the battery charge status regularly when not in use, recharge it to 100% if the load is less than 20% (1 indicator light on the charge gauge). Check the load at least every month and have it fully charged every 6 months.
- It is not recommended to keep the battery connected to the charger for a long period.
- If the battery remains uncharged for a long time, it can lose a significant part of its effectiveness.
- Store the battery in a well-ventilated and dry place. Pay attention to moisture.
- In case of poor conditions, remove the battery from the bike and store it in a dry place until next use.
- The battery can be stored at temperatures between -10°C and 40°C. For long service life, store it at a temperature close to 20°C.
- Monitor the storage temperature and try to avoid discrepancies. For example, do not leave the battery in your car during summer or leave the battery outdoors during a storm in winter.
- It is recommended to store a battery which is not connected to the bike.

**Follow the transport instructions for your PAB:**

- Remove the battery, the control screen and (if necessary) the baskets, arrange them elsewhere in a vehicle during transport.
- Comply with local laws regarding transportation of the PAB.
- A PAB is heavier than a normal bike, so you must be careful when transporting it. Check that the maximum load of the rack, roof or bike rack used is respected. Refer to the support manual used.
- The Li-Ion battery of your PAB, due to its size, is considered a "Class 9 dangerous goods" during transport. Applicable regulations could limit transport of a separate Li-Ion battery (when the battery is not on the bike) in some places. This regulation applies to several airlines and a number of road transport companies. On the other hand, if you are planning to move around with a full PAB (when the battery is on the bike), regulations are less strict. In case you use these transport methods, check the regulations that apply to your PAB with your transport company, before booking.

**Visit your authorized Devinci retailer for regular maintenance of your new PAB:**

- Only your retailer has the know-how and the proper equipment to maintain your PAB.
- If you have any questions about your PAB, please ask for assistance from your retailer!



## ABOUT OUR MANUALS

Our user manuals meet EN 15194, 14766 standards.

Like many sports, cycling involves risk of injury and accidents, so you must be fully aware of these risks. Neither the manufacturer, the retailer, nor the person who sold you the bike, nor the people who maintain the trails are responsible for these risks. As you are solely responsible, it is, therefore, essential that you read and fully understand all the parts contained in this manual and the user manual.

To enjoy maximum safety and enjoyment right from the get go, it is important that you are familiar with your new bike, its handling and its possibilities. It is your duty to maintain your bike well and reduce the risk of injury. Biking can be a dangerous activity, even under the best conditions. There are risks associated with using a bicycle that cannot be predicted or avoided. These are the sole responsibility of the cyclist.



## YOUR AUTHORIZED DEVINCI DEALER

Your authorized Devinci retailer is at your service to guide your choices of bike and accessories which are best suited to the style of biking you wish to perform. This will help you maintain your equipment in good condition so that you can take full advantage of your investment. The staff at your authorized Devinci retailer have the training, experience and tools to carry out the right repairs and provide you with reliable advice.

However, your authorized Devinci retailer cannot make decisions for you, and cannot be held responsible for your lack of knowledge, experience, qualification or common sense. However, it will take the necessary time to explain the operation of a component or to help you choose an accessory that meets your specific needs.

For further information, please see the **User Manual** available on the Devinci website and the **Shimano STEPS EP800 & E7000 series user manual** available on <http://si.shimano.com/>. You can ask your authorized Devinci retailer. He will take the time to answer any questions you may have and will advise you, with great pleasure.

To learn more about your bike's warranty, refer to the User Manual under the "Ride in Peace with the Devinci Warranty" tab.





#### **ASSEMBLY INSTRUCTIONS:**


- 1- THOROUGHLY CLEAN THE INTERIOR OF EACH BEARING HOUSING TO REMOVE ANY DIRT OR OLD GREASE;
- 2- APPLY HIGH QUALITY WATERPROOF GREASE ON THE INSIDE FACE AND INSIDE DIAMETER OF ALL BEARING HOUSINGS BEFORE PRESS-FIT;
- 3- APPLY HIGH QUALITY WATERPROOF GREASE TO ALL PIVOT PARTS THAT CONTACT WITH THE INNER DIAMETER OF THE BEARINGS.
- 4- APPLY HIGH QUALITY WATERPROOF GREASE TO ALL NON-THREADED METAL-TO-METAL INTERFACES (EX.: PLANAR FACE OF THE PIVOT SPACER THAT CONTACTS THE LATERAL FACES OF THE FRONT TRIANGLE WL PIVOT). THESE INSTRUCTIONS ALSO APPLY TO THE SHOCK ASSEMBLY;
- 5- UNLESS OTHERWISE SPECIFIED, APPLY BLUE LOCTITE 242 ON ALL THREADS BEFORE ASSEMBLY TO THE SPECIFIED TORQUE VALUE;
- 6- TO PREVENT DAMAGE TO THE FRAME, THE SEATPOST MUST HAVE A MINIMUM INSERTION IN THE SEAT TUBE.

#### **ALUMINIUM FRAME:**

SMALL / MEDIUM / LARGE / X-LARGE - 100mm INSERTION

\*ALWAYS VERIFY CONNECTOR CLEARANCE BEFORE FULLY INSERTING A DROPPER POST.

7- **FRG ADJUSTABLE:** THIS DESIGN ALLOWS RIDERS TO CHOOSE BETWEEN A LOW OR HIGH POSITION. WITH FRG ADJUSTABLE TECHNOLOGY, YOU CAN FINE-TUNE YOUR RIDE TO PERSONAL TASTES OR SPECIFIC TRAIL TYPES USING A FLIP-FLOP PIVOT MECHANISM THAT SLIGHTLY CHANGES THE BIKE'S GEOMETRY AS SHOWN BELOW.



#### **CLEANING INSTRUCTIONS:**

IT IS A WELL KNOWN FACT THAT A CLEAN BIKE PERFORMS BETTER. DEVINCI RECOMMENDS WASHING YOUR BIKE REGULARLY USING A BRUSH AND SOAPY WATER. HOWEVER, DEVINCI DO NOT RECOMMEND THE USE OF A PRESSURE WASHER, SINCE THIS MAY SIGNIFICANTLY REDUCE THE SERVICE LIFE OF BALL BEARINGS. EVEN THOUGH OUR BALL BEARINGS ARE EQUIPPED WITH HIGH QUALITY DOUBLE-LIP SEALS, HIGH PRESSURE WATER CAN STILL PASS THESE SEALS AND REMOVE THE GREASE INSIDE THE BEARING. THIS MAY CAUSE PREMATURE CORROSION AND WEAR OF THE BALL BEARINGS.